

RIDA Petrol Engine Oil API SL SAE 15W-50

- Anti-wear protection
- Oxidation resistance
- Excellent cleaning power
- Long drain interval protection
- Lower Fuel Consumption

RIDA Petrol Engine Oil SAE 15W-50 is a premium quality synthetic lubricating oils fully engineered for use in all types of petrol automobile engines. The synthetic base fluids in combination with the advance additive system provide the outmost wear protection and excellent thermo-oxidative stability. RIDA Petrol Engine Oil SAE 15W-50 is also approved by leading car manufacturers and meets the latest industry standards for service fill use.

Designed to Perform

Oxidation Resistance – RIDA Petrol Engine Oil SAE 15W-50 provides a good oxidation stability that reduced engine deposits and sludge build up, the advance anti-oxidant additive present slows down the oil degradation ensuring longer maintenance intervals.

Anti-wear, Anti-corrosion & Anti-rust Protection – Longer Equipment Life, proven anti wear, anti-corrosion and anti-rust additive packages provide greater resistance and extend engine life and provides low maintenance costs. These properties of RIDA Petrol Engine Oil SAE 15W-50 Oils prevent rust development by creating a thin film on the engine metal surfaces or any adjacent component of thus preventing the moisture absorption of its metal parts.

High Viscosity Index – Boost Energy Efficiency high viscosity oil engineered to protect against metal-to-metal contact. It maintains the optimum viscosity and resist shearing on the longer run, and in a wide range of working temperature. Consequently, the reduced viscosity at lower temperatures improves the

ability of a vehicle to start and helps to lower fuel consumption.

Advance Detergent Additive System – Improves Engine Cleanliness. These additives help to remove impurities that travel to the oil filter while also cleaning existing deposits and foreign substances in the engine. This increase in engine cleanliness helps to reduce the damage these contaminants may have caused.

Performance Characteristics

RIDA Petrol Engine Oil SAE 15W-50 has a premium protection Motor Oil is specially formulated to provide superior protection and performance in a wide variety of demanding applications. It exceeds the needs of large and small gasoline or diesel engines in cars, motorcycles, trucks, motors, maintenance equipment, heavy equipment, street rods applications and it is ideal for high mileage vehicles. RIDA Petrol Engine Oil SAE 15W-50 provides flexibility and performance beyond conventional oils for convenience and trouble free operation.

Typical Physical Characteristics

Property	Temp	Units	Test Methods	API SL 15W-50
Kinematic Viscosity	@ 100°C	cSt	ASTM D445	19.05
Kinematic Viscosity	@ 40°C	cSt	ASTM D445	135
Density	@ 15 °C	kg/l	ASTM 4052	0.871
Flash Point (COC)		°C	ASTM D92	220
Pour Point		°C	ASTM D97	-32

These characteristics are typical of current product methods whilst future production will conform to RIDA Lubricants specifications, variations in these physical characteristics may occur.

Technical Data Sheet (TDS)



Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on health and safety is available on the appropriate Material Safety Data Sheet (MSDS) which can be obtained from www.ridalubs.com

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

Additional Information

- Technical advice on any applications not covered here may be obtained from your RIDA Lubricants Representative.
-