

# PRADO LUBRICANTS



# ABOUT US

Prado Lubricants is a UAE based company that offers full range of lubricants and greases for various industries, including automotive, industrial, marine, and aviation applications. We at Rida prove our selves in offering high-quality lubricants that meet and exceed industry standards, and we have a team of experienced professionals which can provide technical support to customers 24/7.



## OUR VISION

Become the leading Manufacturer and Marketer of Lubricants, Greases & Base Oils by striving for excellence. Continue to reach out for greater heights by continuous improvement utilizing technological innovation to improve product quality and serving the clients' needs at all time while adhering to latest international norms.



## OUR VALUE

- Integrity
- Innovation
- Transparency
- Commitment
- Teamwork
- Customer Satisfaction

# عن الشركة

برادو للزيوت هي شركة رائدة مقرها دولة الإمارات العربية المتحدة. تقدم مجموعة كاملة من الزيوت و الشحوم لمختلف الصناعات بما في ذلك السيارات و المعدات بمختلف انواعها. نحن في رضا نثبت انفسنا في تقديم مواد تشحيم عالية الجودة تلي معايير الصناعة و لدينا فريق عمل من المحترفين ذوي الخبرة الذين يمكنهم تقديم الدعم الفني للعملاء على مدار الساعة طوال أيام الأسبوع.

## رؤيتنا

تصبح الشركة المصنعة الرائدة و تسويق زيوت التشحيم والشحوم والزيوت الأساسية من خلال السعي لتحقيق التميز. الاستمرار في الوصول إلى مستويات أعلى من خلال التحسين المستمر باستخدام الابتكار التكنولوجي لتحسين جودة المنتج وخدمة احتياجات العملاء في جميع الأوقات الالتزام بأحدث المعايير الدولية.

## قيمنا

- نزاهة
- ابتكار
- الشفافية
- التزام
- العمل بروح الفريق الواحد
- رضا العملاء

# OUR LABORATORIES

Our laboratory is equipped with the most advanced international testing equipments available in the market. We take pride in selecting a team of highly experienced professionals who are passionate about their work.

Our commitment to excellence is reflected in high caliber standards that we maintain. We strive to provide our customers with best possible service and quality standards. We believe in continuous improvement and are constantly updating our processes to ensure that we stay ahead of the curve in the industry.

## مختبراتنا

تم تجهيز مختبرنا بأحدث معدات الاختبار الدولية المتوفرة في السوق. نحن نفخر باختيار فريق من المهنيين ذوي الخبرة العالية والمتحمسين لعملهم.

وينعكس التزامنا بالتميز في المعايير العالية الجودة التي نحافظ عليها. نسعى جاهدين لتزويد عملائنا بأفضل معايير الخدمة والجودة الممكنة. و نؤمن بالتحسين المستمر ونقوم بتحديث عملياتنا باستمرار لضمان بقائنا في صدارة الصناعة.





SAIL - Services to Associations and Industry in the Lubricants sector  
40 Rue Belliard  
1040 Brussels  
Belgium

## EELQMS LETTER OF CONFORMANCE

Hereby SAIL confirms that *Rida Lubricants LLC* hereinafter referred to as "The Company", with address at **91 Hassan bin haitham st., Industrial area 2,, Ajman, 9000 Ajman, AE** has paid the annual fee for the EELQMS Letter of Conformance program

By submitting the Letter of Conformance, registering the company information on the website and payment of the fee, the Company is entitled to claim ACEA specifications.

The company name is listed in the SAIL List of Participants in the EELQMS which will be made available by SAIL to any interested party and published on the SAIL website [www.sail-europe.eu](http://www.sail-europe.eu)

Participation in the European Engine Lubricant Quality Management System (EELQMS) implies a commitment to develop and manufacture those engine lubricants for which compliance with ACEA Oil Sequences will be claimed, or to have such engine lubricants developed or blended by third parties, in accordance with the guidelines, described in the ATIEL Code of Practice, as well as a commitment to ensure an independent audit of the development and manufacturing process.

The commitments referred to apply to the brands in the following list, owned or managed by The Company that make ACEA claims: ***Rida Lubricants / Predo Lubricants / Akzoil Additives***

SAIL assumes no responsibility for the implementation by the Company of its obligations, as defined in the Letter of Conformance, or for any damage that a breach thereof may cause to third parties.

SAIL cannot be held responsible for any claims resulting from inclusion and non-inclusion of the entity. SAIL also declines any responsibility with regard to the external audit procedure, which belongs to the domain of the relevant auditor

Michael Boyer  
SAIL Administrator



## Certificate

QAQC hereby certifies that

**PRADO LUBS – F.Z.E,  
RIDA LUBRICANTS LLC**

P.O. Box # 40413, Ajman, UAE

*Has been audited by QAQC and has implemented*

*Quality Management System*

## ISO 9001:2015

**Scope of Registration**

**All Kind of Industrial Oil Lubricants Manufacturing**

Registration Date : 08 Aug. 2016  
Next Audit Date : 07 Aug. 2026  
Expiry Date : 07 Aug. 2026  
Certificate No : AE-0363-EC



*Alex Daniel*  
Chief Executive

This is to certify that the company has been found to conform to the above mentioned standard.  
To verify the validity of this certificate, please visit: [www.qaqcinternational.org](http://www.qaqcinternational.org) or scan the above QR Code.

Quality Accreditation Bureau for Qualified Companies: 30 N, Gould St, Sheridan WY 82801, USA.  
Accreditation by conformity standard international, USA. [www.csiusa.org](http://www.csiusa.org)

License No: 3827

## SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and  
**RIDA LUBRICANTS LLC**  
 may be used through 31-Mar-2026 are as follows:

### API SERVICE SYMBOL

Licensee is authorized to display the API Certification Mark on the following products:



BRAND NAME	SAE VISCOSITY GRADE	API SERVICE CATEGORY	CLASSIFICATION
ZARCO LUBE	10W-30	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANTS	15W-40	SN/CI-4	CI-4 PLUS
AKZOIL LUBS	0W-20	SN	
AKZOIL LUBS	10W-40	SN	
LIBERTY LUBE	0W-20	SN	
LIBERTY LUBE	5W-30	SN	
LIBERTY LUBE	10W-40	SN	
RIDA LUBS	0W-20	SN	
RIDA LUBS	10W-40	SN	
RIDA LUBS	20W-50	SN	
ZARCO LUBE	0W-20	SN	
ZARCO LUBE	10W-40	SN	
RIDA LUBS	10W-40	SL	
RIDA LUBS	15W-40	CJ-4	CI-4 PLUS
AKZOIL LUBS	15W-40	CI-4/SN	
PRADO LUBS	15W-40	CI-4	
RIDA LUBS	10W-30	CI-4	
RIDA LUBS	15W-40	CI-4	

Manager - EOLCS/DEF/MOM

Date: 29-Mar-2025

Engine Oil Licensing and Certification System

Copyright 2020 - American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark ("Starburst"), the API Service Symbol ("Donut"), and the API Certification Mark ("Shield") are either trademarks or registered trademarks of API. 2020-142 | 02.20

To verify the authenticity of this document, go to: [engineoil.api.org/Directory/EolcsSearch](http://engineoil.api.org/Directory/EolcsSearch)

License No: 3827

## SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and  
**RIDA LUBRICANTS LLC**  
 may be used through 31-Mar-2026 are as follows:

### API SERVICE SYMBOL

Licensee is authorized to display the API Certification Mark on the following products:



BRAND NAME	SAE VISCOSITY GRADE	API SERVICE CATEGORY	CLASSIFICATION
GCC LUBRICANTS	5W-30	SP	Resource Conserving, SN PLUS
GCC LUBRICANTS	10W-30	SP	Resource Conserving, SN PLUS
LIBERTY LUBE	5W-20	SP	Resource Conserving, SN PLUS
LIBERTY LUBE	10W-30	SP	Resource Conserving, SN PLUS
PREDO LUBS	0W-16	SP	Resource Conserving, SN PLUS
PREDO LUBS	0W-20	SP	Resource Conserving, SN PLUS
PREDO LUBS	5W-20	SP	Resource Conserving, SN PLUS
PREDO LUBS	10W-30	SP	Resource Conserving, SN PLUS
RIDA LUBS	0W-16	SP	Resource Conserving, SN PLUS
RIDA LUBS	5W-20	SP	Resource Conserving, SN PLUS
RIDA LUBS	10W-30	SP	Resource Conserving, SN PLUS
ZARCO LUBE	5W-20	SP	Resource Conserving, SN PLUS
ZARCO LUBE	5W-30	SP	Resource Conserving, SN PLUS

Engine Oil Licensing and Certification System

Copyright 2020 - American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark ("Starburst"), the API Service Symbol ("Donut"), and the API Certification Mark ("Shield") are either trademarks or registered trademarks of API. 2020-142 | 02.20

*Bill O'Keefe*

Manager - EOLCS/DEF/MOM

Date: 29-Mar-2025

To verify the authenticity of this document, go to: [engineoil.api.org/Directory/EolcsSearch](http://engineoil.api.org/Directory/EolcsSearch)

License No: 3827

## SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and  
**RIDA LUBRICANTS LLC**  
 may be used through 31-Mar-2026 are as follows:

### API SERVICE SYMBOL

Licensee is authorized to display the API Certification Mark on the following products:



BRAND NAME	SAE VISCOSITY GRADE	API SERVICE CATEGORY	CLASSIFICATION
AKZOIL LUBS	0W-16	SP	Resource Conserving, SN PLUS
AKZOIL LUBS	0W-20	SP	Resource Conserving, SN PLUS
AKZOIL LUBS	5W-20	SP	Resource Conserving, SN PLUS
AKZOIL LUBS	5W-30	SP	Resource Conserving, SN PLUS
AKZOIL LUBS	10W-30	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANT	5W-20	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANTS	0W-16	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANTS	0W-20	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANTS	5W-30	SP	Resource Conserving, SN PLUS
ANDOIL LUBRICANTS	10W-30	SP	Resource Conserving, SN PLUS
GCC LUBRICANTS	0W-16	SP	Resource Conserving, SN PLUS
GCC LUBRICANTS	0W-20	SP	Resource Conserving, SN PLUS
GCC LUBRICANTS	5W-20	SP	Resource Conserving, SN PLUS

Manager - EOLCS/DEF/MOM

Date: 29-Mar-2025

Engine Oil Licensing and Certification System

Copyright 2020 - American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark ("Starburst"), the API Service Symbol ("Donut"), and the API Certification Mark ("Shield") are either trademarks or registered trademarks of API. 2020-142 | 02.20

To verify the authenticity of this document, go to: [engineoil.api.org/Directory/EolcsSearch](http://engineoil.api.org/Directory/EolcsSearch)

License No: 3827

## SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and  
**RIDA LUBRICANTS LLC**  
 may be used through 31-Mar-2026 are as follows:

### API CERTIFICATION MARK

Licensee is authorized to display the API Certification Mark on the following products:



BRAND NAME	SAE VISCOSITY GRADE	ILSAC SPECIFICATION
AKZOIL LUBS	0W-20	GF-6A
AKZOIL LUBS	5W-20	GF-6A
AKZOIL LUBS	5W-30	GF-6A
AKZOIL LUBS	10W-30	GF-6A
ANDOIL LUBRICANT	5W-20	GF-6A
ANDOIL LUBRICANTS	0W-20	GF-6A
ANDOIL LUBRICANTS	5W-30	GF-6A
ANDOIL LUBRICANTS	10W-30	GF-6A
GCC LUBRICANTS	0W-20	GF-6A
GCC LUBRICANTS	5W-20	GF-6A
GCC LUBRICANTS	5W-30	GF-6A
GCC LUBRICANTS	10W-30	GF-6A
LIBERTY LUBE	10W-30	GF-6A
PREDO LUBS	0W-20	GF-6A
PREDO LUBS	10W-30	GF-6A
RIDA LUBS	5W-20	GF-6A
RIDA LUBS	10W-30	GF-6A
ZARCO LUBE	5W-20	GF-6A
ZARCO LUBE	5W-30	GF-6A
ZARCO LUBE	10W-30	GF-6A

Manager - EOLCS/DEF/MOM

Date: 29-Mar-2025

Engine Oil Licensing and Certification System

Copyright 2020 - American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark ("Starburst"), the API Service Symbol ("Donut"), and the API Certification Mark ("Shield") are either trademarks or registered trademarks of API. 2020-342 | 02.20

To verify the authenticity of this document, go to: [engineoil.api.org/Directory/EolcsSearch](http://engineoil.api.org/Directory/EolcsSearch)

License No: 3827

## SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and  
**RIDA LUBRICANTS LLC**  
 may be used through 31-Mar-2026 are as follows:



### API CERTIFICATION MARK

Licensee is authorized to display the API Certification Mark on the following products:

BRAND NAME	SAE VISCOSITY GRADE	ILSAC SPECIFICATION
AKZOIL LUBS	0W-16	GF-6B
PREDO LUBS	0W-16	GF-6B
RIDA LUBS	0W-16	GF-6B

Engine Oil Licensing and Certification System

Copyright 2020 - American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark ("Starburst"), the API Service Symbol ("Donut"), and the API Certification Mark ("Shield") are either trademarks or registered trademarks of API. 2020-142 | 02.20

To verify the authenticity of this document, go to: [engineoil.api.org/Directory/EolcsSearch](http://engineoil.api.org/Directory/EolcsSearch)

Manager - EOLCS/DEF/MOM

Date: 29-Mar-2025

# **RADO** LUBRICANTS



**100%**  
Customer Satisfaction Promised



# GASOLINE / DIESEL ENGINE OILS



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## GASOLINE ENGINE OILS

## زيوت محركات البنزين

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
0W20	46	8.25	155	232	-39	* API SL, SM, SN
5W30	57.8	10.2	166	240	-39	* API SL, SM, SN
5W40	85.3	14.3	174	242	-39	
10W40	105	14.9	148	228	-36	* API SL, SM, SN
20W50	160	19.1	136	242	-29	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## DIESEL ENGINE OILS

## زيوت محركات الديزل

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
5W30	64	10.5	153	224	-39	* API CH, CI, CJ, CK *ACEA A3/B4
5W40	103	14.9	151	238	-39	
10W40	92.5	14.3	160	242	-39	* API CH, CI, CJ, CK *ACEA A3/B4
15W40	103	14.5	145	234	-32	* API CH, CI, CJ, CK *ACEA A3/B4
20W50	155	19.1	140	248	-30	* API CH, CI, CJ, CK *ACEA A3/B4

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

# GEAR OILS / TRACTOR FLUID / ATF

## GEAR OILS

## زيوت التروس

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
SAE 90	161	15.5	95	230	-33	GL-4, GL-5
SAE 140	204	18.0	95	310	-12	
80W90	136	14.5	105	202	-30	
80W140	188.9	25	165	225	-38	
85W140	410	28.9	96	210	-15	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## TRACTOR FLUID

## سائل الجرار

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
GL-5	69.3	10.4	136	230	-36	GL-4, GL-5

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## ATF (Automatic Transmission Fluid)

## السائل ناقل حركة أوتوماتيكي

DEX Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
ATF II	28.0	5.8	160	222	-51	Dexron - 2
ATF III	38.0	7.6	175	226	-45	Dexron - 3
CVT Fluid	34.2	7.1	179	214	-51	Suitable for use where Dexron VI is required

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## MOTORCYCLE OILS

## زيوت الدرجات النارية

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
4T	98.5	14.5	152	226	-40	For 4-strokes engine motorcycles. JASO MA MA2 API SN
10W40	108.1	14.6	139	236	-36	
20W50	160.5	18.8	132	248	-33	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## COMPRESSOR OILS

## زيوت الضاغط

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 32	0.860	32.0	5.5	108	230	-30	1a	*Reciprocating type compressors
ISO VG 46	0.867	46.0	7.0	109	234	-30	1a	
ISO VG 68	0.872	68.0	9.0	107	236	-27	1a	
ISO VG 32	0.860	32.0	5.5	108	230	-30	1a	*Rotary type compressors
ISO VG 46	0.867	46.0	7.0	109	234	-30	1a	
ISO VG 68	0.872	68.0	9.0	107	236	-27	1a	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## ANTIFREEZE COOLANT

## سائل تبريد المحرك

Concentration (%)		Freezing Point (°C)
Water (%)	A/F (%)	
0(%)	100(%)	-20°C
70(%)	30(%)	-17°C
50(%)	50(%)	-36°C
40(%)	60(%)	-52°C
30(%)	70(%)	-18°C

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

# HYDRAULIC OILS / MACHINE OILS

## HYDRAULIC OILS

## زيوت هيدروليكية

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG32	0.858	32.0	5.5	108	228	-33	1a	*Anti-wear type (AW Type) *General purpose *General hydraulic system oil circulation system. compressor & bearing oils
ISO VG 46	0.862	46.0	7.1	113	234	-30	1a	
ISO VG 68	0.871	68.0	9.1	109	238	-30	1a	
ISO VG 100	0.878	96.0	11.3	104	240	-27	1a	
ISO VG 150	0.880	150.0	15.3	103	246	-24	1a	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## BRAKE FLUID

## زيت الفرامل

Type	K.Viscosity(cSt)		Corrosion test 120 Hrs.	ERPB	pH	Wet ERBP	Application
	40 °C	100 °C					
DOT 3	1300	2.4	Pass	238	9	148	* For use in automotive disc, drum and anti-skid brake systems and clutch systems.
DOT 4	1250	2.1	Pass	270	8	170	* For hydraulic disc brakes and drum brakes on motorcycles, cars, commercial vehicles and machines.

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## MACHINE OILS

## زيوت الآلات

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 10	0.830	10.0	2.7	108	179	-45	1a	*High speed spindle bearing
ISO VG 15	0.830	15.0	3.5	112	208	-39	1a	
ISO VG 22	0.842	22.0	4.37	107	224	-27	1a	
ISO VG 68	0.870	68.0	8.92	105	240	-24	1a	*Multi-purpose industrial oil
ISO VG 100	0.878	100.0	11.7	105	248	-21	1a	
ISO VG 150	0.880	150.0	15.2	102	252	-12	1a	
ISO VG 220	0.885	220.0	19.5	101	256	-12	1a	
ISO VG 320	0.890	320.0	25	100	260	-9	1a	
ISO VG 460	0.890	460.0	30.9	97	266	-9	1a	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**20L, 208L**

# INDUSTRIAL GEAR OILS / HEAT TRANSFER OIL



**AVAILABLE PACKING**

**1L, 4L, 5L, 20L, 208L**

## INDUSTRIAL GEAR OILS

## زيوت التروس الصناعية

ISO Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 68	0.870	68.0	8.8	102.0	242	-27	1b	*Multi-purpose EP industrial oil
ISO VG 100	0.880	100.0	11.5	102.0	248	-27	1b	
ISO VG 150	0.880	150.0	15.1	101.0	252	-27	1b	
ISO VG 220	0.890	220.0	19.5	101.0	256	-24	1b	
ISO VG 320	0.895	320.0	24.9	100.0	270	-24	1b	
ISO VG 460	0.901	460.0	31.7	100.0	276	-21	1b	
ISO VG 680	0.901	680.0	43.0	106.0	282	-21	1b	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



**AVAILABLE PACKING**

**20L, 208L**

## HEAT TRANSFER OIL

## زيت نقل الحرارة

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 32	0.850	32.0	5.5	108	230	-15	1a	*Various kinds of oil application for heat transfer
ISO VG 46	0.860	46.0	7.0	109	250	-15	1a	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## TRANSFORMER OIL

## زيت المحولات

API Viscosity	K.Viscosity (cSt) 40 °C	Viscosity Index	Flash Point (PMCC)	Pour Point	Before Treatment	After Treatment	Application
Inhibited	8.9	≥110	≥150	-30	>30	>70	*Transformer oil is used to insulate high-voltage electrical infrastructure such as transformers, capacitors, switches and circuit breakers.
Uninhibited I	15.0	≥110	≥150	-36	>30	>70	
Uninhibited II	10.0	≥110	≥150	-48	>30	>70	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

# MARINE ENGINE OIL / SLIDEWAY OILS

## MARINE ENGINE OIL

## زيت المحرك البحري

API Viscosity	K.Viscosity(cSt)		VI	TBN	Flash Point °C	Pour Point °C	Application
	100°C						
SAE 30	9.3		≥95	40	≥230	-12	* All types of marine engines
SAE 40	12.5		≥95	40	≥230	-9	
SAE 50	16.3		≥95	40	≥230	-6	

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## SOLUBLE CUTTING OIL

## زيوت القطع القابلة للذوبان

Cutting Oil	Specific gravity (15/4°C)	K.Viscosity(cSt)		Emulsion Type	Corrosion Test	pH at 3% Emulsion	Refractometer correction Factor	Application
		40°C	100°C					
Soluble Cutting Oil	0.95	>40.0	>6.0	Milky	3	9.1	1	*fabricating, forming, stamping, turning, milling sawing, bending, broaching and tapping.

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## THREAD CUTTING OIL

## زيت قطع الخيط

Cutting Oil	K.Viscosity(cSt)		Copper Strip Corrosion for 3 Hrs.	Flash Point	Active Sulphur	Application
	40°C					
Thread Cutting Oil	32		1a	>215	Nil	*lubricate, dissipate heat, from the tool and workpiece, and remove chips during the cutting process.

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## NEAT CUTTING OIL

## زيت قطع المنظم

Cutting Oil	K.Viscosity(cSt)		Copper Strip Corrosion for 3 Hrs.	Flash Point	Active Sulphur	Application
	40°C					
Neat Cutting Oil	36		1a	>215	Nil	* light machining to heavy-duty operations, eg., gear hobbing, broaching, turning, honing and drilling.

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

## SLIDEWAY OILS

## زيوت الممرات المنزلقة

API Viscosity	Specific gravity (15/4°C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40°C	100°C					
ISO VG 32	0.860	32.0	5.9	130	230	-36	1a	*Slideway and hydraulic oil for lightly loaded machining equipments
ISO VG 68	0.874	68.0	9.7	124	248	-27	1a	*Slideway for medium and heavy loaded equipments
ISO VG 100	0.885	220.0	20.5	248	252	-24	1a	*Vertical or heavily loaded slideway oil

\*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

# MULTI-PURPOSE GREASE

## MULTI-PURPOSE GREASE

## شحم متعدد الأغراض



Color	Soap	Penetration (NLGL)	Melting Point (°C)	Oil Separation	Oxidation Stability	Copper Corrosion	Service Temp	Properties	Application
Dark Brown	Lithium	00 (415)	190	8.5	0.25	PASS	-30.0°C ~120°C	*High EP *Good Antiwear *Oxidation stability *Corrosion control *Rust preventative *Good water-washout characteristic	*Central grease feeding system *EP point *Concrete pump-car
		0 (370)	195	7.5	0.25	PASS	-30.0°C ~120°C		
		1 (320)	202	5.0	0.25	PASS	-30.0°C ~130°C		
		2 (270)	208	2.5	0.25	PASS	-30.0°C ~130°C		
		3 (235)	208	1.5	0.25	PASS	-30.0°C ~130°C		
Red	Lithium	2 (270)	210		0.25	PASS	-30.0°C ~140°C	*Excellent coherence *Good	*Where noise - reducing water resisting lubricating area *Rolling bearing or sliding area requiring sealing
Blue		2 (270)	210		0.25	PASS	-30.0°C ~140°C		
Black	Lithium	2 (270)	220		0.25	PASS	-30.0°C ~150°C	*Very high EP *Anti-wear *Usable under severely high load	*Automotive CVJ *Anti-wear for various bearings *Joint and spline shaft *EP and antiwear required

**AVAILABLE PACKING**  
0.5Kg, 1Kg, 15Kg, 180Kg

# SPECIAL GREASES

## SPECIAL GREASES

## شحومات خاصة

### High-speed, Hi-temp & Heavy Load Grease

Color	Soap	Penetration (NLGL)	Melting Point (°C)	Copper Corrosion	Service Temp	Properties	Application
Gray black	Inorganic	2	NONE	PASS	-40.0°C ~280°C	*Not carbonized at high temp *Tenacious lubricating	*Fan, coating roll, furnace, heat blower, tender, klin, painting line trolley, C&L calendar machine & etc...
Black	Inorganic	2	NONE	PASS	-45.0°C ~290°C	*Long life under hi-temp *Keep lubricating under hot steam	



### Synthetic Grease Lithium-Complex Base

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Red	Smooth	265	6	PASS	265-295	1-2	*Operating under high loads and temperatures, heavy machinery, couplings and transmission shafts.

### Lithium - Complex Grease

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Red	Smooth	265	6	PASS	265-295	1-2	Automotive, agricultural, construction, industry, mining, paper and steel mills.



### Calcium Sulfonate Grease

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Pale Yellow	Smooth	90 -110	<5	PASS	265-295	1-2	Automotive, agricultural, construction, industry, mining, paper and steel mills.

### High Speed Synthetic Grease

Color	Soap	Penetration (NLGL)	Melting Point (°C)	Copper Corrosion	Service Temp	Properties	Application
White	Lithium	2	200	PASS	-40.0°C ~130°C	*No splash at high speed *Low temp characteristics *Compatible with plastics	*Textile machine, machine tool spindle, optical machine, precision machine & etc...
White	Lithium	2	200	PASS	-50.0°C ~140°C		



**AVAILABLE PACKING**  
0.5Kg, 1Kg, 15Kg, 180Kg

# PRADO LUBRICANTS

## Table of Contents

## جدول المحتويات

- ▶ GASOLINE / DIESEL ENGINE OILS ◀ زيوت محركات البنزين والديزل
- ▶ GEAR & ATF LUBRICANTS ◀ زيوت التروس والسائل ناقل حركة أوتوماتيكي
- ▶ MOTORCYCLES LUBRICANTS ◀ زيوت تشحيم الدراجات النارية
- ▶ HYDRAULIC OILS / MACHINE OILS ◀ الزيوت الهيدروليكية / زيوت الآلات
- ▶ INDUSTRIALS LUBRICANTS ◀ زيوت التشحيم الصناعية
- ▶ MARINE LUBRICANTS ◀ زيوت التشحيم البحرية
- ▶ MULTI-PURPOSE GREASES ◀ شحم متعدد الأغراض
- ▶ SPECIALITY LUBRICANTS ◀ الشحوم الخاصة



AUTOMOTIVE



MOTORCYCLE



TRANSPORT



MINING



MARINE



AGRICULTURE



INDUSTRIAL



FORESTRY

# THE HOUSE OF WORLD CLASS & **EXCELLENT** LUBRICANTS



## MAKING THE RIGHT CHOICE

**'GOOD'** engine oils are conventional mineral based engine oils suitable for the everyday driver. Standard service conditions specified in the owner's manual can be met with this range of products.

**'BETTER'** engine oils are synthetic blends. They provide more protection than conventional or 'good' grades. These oils are suitable for severe service conditions where a vehicle may endure stop-start driving or short trips, long idling periods, towing of heavy loads (such as boats, trailers or driving a utility) or may require long drain capabilities.

**'BEST'** engine oils are full synthetic grades that offer superior protection. Severe and high performance applications can be met with this range. If you want the ultimate protection for your engine, Rida recommends the use of fully synthetic lubricants.

# THE HOUSE OF WORLD CLASS & **EXCELLENT** LUBRICANTS





**HEAD OFFICE**

 Toll Free Number : 800-5334, Telephone : 06 749 2994, Mobile : +971 56 103 1399, P.O.Box : 40413  
Ind. Area 2, Ajman, United Arab Emirates